

# CLAMPMITTER™

*cut the cord*



**TORONICS™**  
Authorized Canadian distributor



## *Safety, Convenience, Productivity*

The CLAMPMITTER™ is a unique tool for inductive coupling. This self-contained inductive transmitter increases productivity, promotes safety and simplifies locates by condensing the transmitter and inductive coupler into one cordless package. Whether climbing down a manhole or accessing a utility box, the Clampmitter is an easy alternative to suiting up with a full transmitter and wired coupler.

- Eliminates the risks of hauling heavy transmitter boxes down aging manhole ladders
- Removes the hazards of tripping/falling over long cords in unstable job sites
- Lends itself as a back-up transmitter when your line transmitter's battery goes down in the field
- Allows the user to complete more than one locate at once
- Removing the cord permits the user to easily lock the unit inside manholes and switchgears; eliminating theft risks and the need for more than one user to stand watch
- Recharges with ease using a standard USB supply
- Affordable price point to add to budgetary plans
- Made in the USA



9351 East 59th Street • Raytown, MO 64133-3895, USA  
800-851-7347 • 816-353-2100 • FAX 816-353-5050  
rycom@rycominstruments.com • www.rycominstruments.com





*cut the cord*

### *Cut the cord*

For added safety, more convenience and increased productivity, cut the cord. The CLAMPITTER™ is a self-contained, stand-alone, transmitting inductive coupler.

### *Three Frequencies*

The unit is engineered with three highly capable inductive frequencies. These frequencies are commonly available on most locators from a wide range of manufacturers. And, cutting the cord means you don't have to match your output jack to use with a different brand of locator.

### *Compact & Lightweight*

Long trudges in the field feel better when carrying the CLAMPITTER™. This unit is 0.8 pounds and ready for action on its 3 available inductive frequencies. There is no need to worry about hauling that heavy transmitter to the field.

### *High & Low Power Outputs*

Adjustable power settings allow for the just the right amount of signal to be applied. For short runs in congested areas the low power can prevent bleed over. The high power setting will light up the most stubborn and resistive circuits.

### *Rechargeable Battery*

No fumbling for more D-cells to keep your locates rolling. The CLAMPITTER™ can be charged with a simple, standard USB cord (with a whopping 14 hours of continuous use on a full charge!). And there's no messy wall and car chargers falling out of your bag.

### *Hot Stick Ready*

D-ring and 1/4 inch threaded insert for fitting of hotstick and lanyard.



### *Specifications*

Operating Frequencies Model A:	33kHz (32,768Hz), 65kHz (65,536Hz) & 82kHz (82,315Hz)
Operating Frequencies Model B:	33kHz (32,768Hz), 65kHz (65,536Hz) & 83kHz (83,077Hz)
Operating Frequencies Model C:	33kHz (32,768Hz), 65kHz (65,536Hz) & 131kHz (131,072Hz)
Output Power Levels:	Low Power / High Power
Power Source:	Rechargeable Li-Ion Battery
Battery Life:	14 Hours (continuous use)
Charging:	Standard USB supply
Operating Temperature:	-4° F to 140° F (-20° C to 60° C)
Inside Diameter:	.42 Inches (10.67cm)
Dimensions:	5.6" x 10.8" x 1.0" (14.2cm x 27.4cm x 2.4cm)
Weight:	0.8 lbs (0.362kg)
Country of Origin:	United States



9351 East 59th Street • Raytown, MO 64133-3895, USA  
800-851-7347 • 816-353-2100 • FAX 816-353-5050  
rycom@rycominstruments.com • www.rycominstruments.com

Authorized Canadian distributor:  
Toronics Inc Tel: 416-391-0033  
www.toronics.com